



Order form
Purchaser

Valid from August 2013
Order no

Vaisala INTERCAP® Humidity and Temperature Probe HMP60

Vaisala INTERCAP® Humidity and Temperature Probe		HMP60																PRICE
1 Output signals	0...1 V 0...2.5 V 0...5 V 1 ...5V Scaling for 4...20 mA converter (channel 1 only) RS485	A B C D I R																
2 Measured parameter for channel 1	RS485 RH T (-40 ... +60°C) Td (-40 ... +60°C)	0 1 2 3																
3 Measured parameter for channel 2	RS485 or current interface RH T (-40 ... +60°C) Td (-40 ... +60°C)	0 1 2 3																
4 Sensor protection	Plastic grid with filter Plastic grid Stainless steel sintered filter Catalytic filter 232637	A B C D																
5 Accessories	No accessories Pair of plastic nuts Duct installation kit 215619	0 1 3																
6 Humidity sensor	Intericap																	
7 Probe cable length	No cable 60 °C cable 0.3 m HMP50Z032 60 °C cable 3 m HMP50Z30A 180 °C FEP cable 3m 226902 180°C FEP cable 1.5m 238025																	
8 User guide	No user guide Multilingual quick guide																	
9 Loop power converter	No converter 4...20 mA loop power converter Always use single unit package																	
TOTAL																		
QTY																		
TOTAL VALUE																		

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

HMP60	A	1	2	A	0	A	1	B	0
-------	---	---	---	---	---	---	---	---	---